



Single Axle Steel Side Utility Trailer

Sizes Available

4 x 6, 4 x 8, 5 x 8, 5 x 10, 6 x 10, 6 x 12

Standard Features

- Single 2200 lbs or 3500 lbs Axle
- 2" A-Frame Coupler
- 2000 lbs A-Frame Jack
- 13" Wheel & Tire Assembly On 2200 lbs Axle
- 14" Wheel & Tire Assembly On 3500 lbs Axle
- Treated Wood Plank Floor
- Fold Down Rear Ramp
- Full Steel Side
- Gr. 70 Safety Chains c/w Snap Hook
- Top Tie Down Rail & Stake Pockets
- Transport Canada & DOT Approved Lighting
- Maxi-Seal Wire Harness
- Rubber Mounted Sealed Lights
- Sico Two-Part Epoxy Primer
- Sico Two-Part Acrylic Urethane Finish

Specifications

Tire Sizes:	ST175/80D13 LRC (2200 lbs Axle) ST205/75D14 LRC (3500 lbs Axle)
Deck Height:	14" (2200 lbs Axle) 16" (3500 lbs Axle)
Tongue Length:	45"
Side Height:	15" (Incl. Tie Down Rail)

Curb Weight - 2200 lbs Axle


4 x 6:	220 kg (485 lbs)
4 x 8:	240 kg (530 lbs)
5 x 8:	260 kg (570 lbs)
5 x 10:	290 kg (640 lbs)

Curb Weight - 3500 lbs Axle

4 x 8:	260 kg (570 lbs)
5 x 8:	280 kg (610 lbs)
5 x 10:	310 kg (680 lbs)
6 x 10:	340 kg (750 lbs)
6 x 12:	430 kg (950 lbs)



Your Authorized Five Star Trailer Dealer



www.fivestartrailer.com

Specifications or features may change without notice.